



Product model: HPM580 anti-explosion pressure controller

Manufacturer: Nanjing Hangjia Electronic Technology Co., LTD

Product category: pressure switch

Application: hydropower, petroleum, chemical, machinery, hydraulic and other industries

Overview

HPM580 Four-way anti-explosion Pressure Controller adopts high accurate and high stable silicon pressure core as sensitive element. The built-in signal processing circuit can transform and process the front-end signal of the sensor to output IAO and four-way relay switch value. This product combines the measurement, display, output and control together, with the flexibility, easy operation, safety and reliability features, which can be widely used in hydropower, petroleum, chemical, mechanical and hydraulic and other industries.


Features

- 4 bit LED digital tube display
- four-way control point relay output
- field set control point
- 4-20mA standard signal output
- optional power supply 24VDC or 220VAC


Technical Parameters

Pressure Range	-100kPa...0 ~ 0.01...60MPa	Accuracy	0.5%
Overload	150%	Pressure Type	Gauge /Absolute/Sealed pressure
Stability	≤0.1% / year	Power Supply	24VDC/220VAC
Display Mode	0.56" Nixie tube	Display Range	-1999 ~ 9999
Ambient Temperature	-20°C ~ 70°C	Relative Humidity	≤80%
Installment Thread	Optional	Material	Stainless Steel/BP Explosion-proof

Structure Drawings



Electrical Connection



Ordering Guide

Item NO.	Type					
HPM580	Intelligent Pressure Switch					
	Pressure Range	Measuring Range				
	(0~X)kPa	Fill out X directly				
		Code	Output Signal			
		B1	(4~20)mA			
		B9	Relay Output			
		Code	Thread Spec			
		P1	M20x1.5			
		P4	G1/2			
		Code	Electrical Connector			
		C2	Cable Output			
		Code	Structure&Material			
		M1	Diaphragm	Interface	Shell	
		M2	316L	316L	316L	
		M3	Tantalum	Hastelloy	316L	
		M4	Titanium	Titanium	316L	
		Code	Additional Functions			
		G	Gauge Pressure (Default)			
		V1	Supply Voltage 24V DC			
		V2	Supply Voltage 220V AC			
		Kn	Numbers of Pressure Control Points,n=1~4			
		T	High-temperature Resistance Medi			
		W	Water-proof and Ventilated treatmer			
HPM580	(0~20)kPa	B1 B9	P1	C2	M1	G V1 K4

Tips:

1. When ordering products controlled by pressure points, please specify the number of pressure points, the pressure value controlled, and the normally open or normally closed switching points
2. For other special requirements, please contact us and indicate in the order.